



## 2 PANEL FACE UP

## INSTRUCTIONS:

- IA. PEEL FABRIC BACK PAST DESIRED CUT LINE HINT: USE A HEAT GUN TO RELEASE GLUE
- IB. CUT PANEL, FACE UP, WITH A STRAIGHT EDGE AND RAZOR KNIFE (CARE SHOULD BE TAKEN NOT TO CUT FABRIC)
- IC. CUT FABRIC ON A 45° ANGLE INTO CORNER
- 2A. CUT SCRAP PIECE OF FABRIC TO FIT EXPOSED CORE IN THE INSIDE CORNER AND ADHERE INTO PLACE (BUTT PATCH INTO CORNER, DO NOT OVERLAP ONTO FACE)
- 3A. APPLY SPRAY ADHESIVE TO EXPOSED PANEL CORE AND REWRAP FABRIC (ALL FIELD ALTERATIONS REQUIRE I" FABRIC RETURN ON PANEL BACK)
- 3B. PINCH EXCESS FABRIC TOGETHER, ON OUTSIDE CORNER, WITH FINGERS AND CUT OFF FLAP WITH SCISSORS.

WKINETICS
Noise Control

INSIDE CORNER
FIELD CUT AND REWRAP
OF KINETICS WALL PANELS

LAST DATE REVISED

1/10/18

DRAWN BY

DRAWING NO.

T-DWG

DQK

INSTALL46