

S4 Panel is an economical and easily cleanable sound absorber. The S4 panel is constructed from a 3 PCF fiberglass core completely encapsulated with a fiberglass reinforced, aluminized polyester film facing. S4 is available in 1" and 2" thicknesses and panel sizes up to 48" x 120". The S4 panel with aluminized (silver) facing can be used in temperatures from -65° F to 265° F.

The S4 panel is well suited for projects where moisture resistant and economical sound absorber panels are required.

APPLICATIONS:

- Arenas
- Natatoriums
- Dog kennels
- Shooting ranges
- Mechanical equipment rooms
- Workshops



S4 / Wipeable Absorption Panel

DESCRIPTION

· A fully encapsulated moisture resistant fiberglass absorber

ACOUSTICAL PERFORMANCE

Frequency (Hz)	125	250	500	1K	2K	4K	NRC
1" Thick	0.13	0.32	0.95	1.08	0.62	0.46	0.75
2" Thick	0.26	0.80	1.23	1.00	0.71	0.43	0.95

Sound Absorption per ASTM C423 • Type A Mounting

MOUNTING

- S4 Clips
- J-Clips (top and bottom)

COMPOSITION

- 1" or 2" thick 3 PCF fiberglass core
- · Completely wrapped with a neoprenecoated, fiberglass reinforced, aluminized polyester reflective film facing
- Thickness: Film 1.5 mil. At fiber reinforcement 8 mil.









